


B Series Anti-glare Downlight



Feature
1. Anti-glare design, UGR<19. Best lighting performance.
2. Top quality led driver, isolated, Free flicker.
3. Lifetime>5years at least, perfect solution for commercial projects.
Option
1. Emergency kits (30% power with 2-3hours duration)
2. Triac/0-10V/DALI dimmable

Specification					
Model	GR-DL-12WB	GR-DL-15WB	GR-DL-18WB	GR-DL-24WB	GR-DL-30WB
Power	12W	15W	18W	24W	30W
Dimension	Ø130xH60mm	Ø165xH65mm	Ø185xH80mm	Ø220xH90mm	Ø225xH90mm
Output	Ø105-115mm	Ø145-150mm	Ø165-170mm	Ø195-200mm	Ø195-200mm
Samsung chips quantity	SMD 24pcs	SMD 30pcs	SMD36pcs	SMD 48pcs	SMD 60pcs
Lumens output	1000-1100lm	1300-1400lm	1550-1650lm	2050-2100lm	2600-2750lm
Color temperature	3000K WW; 4000-4500K NW ; 6000-6500K CW; The yellow color such as 2000-2500K can be customized				
Input voltage	AC100-240VAC; The low voltage such as DC12V 24V 48V can be customized				
Control gear	Included				
Power factor	>0.6/0.9				
CRI	>82				
IP Grade	IP20 Indoor use only				
Materials	Die-cast aluminum				
Beam angle	90°				
Working temperature	-25°C~+50°C				
Certificates	CE RoHS LVD EMC				

W Series Anti-glare Downlight



Grnled

Dimension



Installation

