

Led Linear High Bay Lights



Grnled



Feature

- 1.Suspension/Surface installation option
- 2.Philips 3030 SMD Chips,110-150lm/W output.
- 3.Meanwell,Moso,Sosen,DONE,ZH famous brand driver options.
- 3.Voltage input 100-240VAC 50/60Hz, DC12V DC24V input optional
- 4.Surge protection up to 6KV.
- 5.Different beam angle optional. 30 60 90 30*70 60*90 60*120°.
- 6.CE RoHS Standard
- 7.Power factor>0.93.
- 8.PIR Sensor function can be customized.
- 9.Emergency kit available.(3Hours duration for 20W power)

Spacification

Model	GR-HB-50WT	GR-HB-100WT	GR-HB-150WT	GR-HB-200WT	GR-HB-250WT	GR-HB-300WT	GR-HB-400WT	GR-HB-500WT
Equavilant Watt	50W	100W	150W	200W	250W	300W	400W	500W
Dimension(mm)	93*353*115	93*620*115	93*887*115	93*1154*115	93*1421*115	230*947*173	230*1214*173	230*1481*173
LED Chips Quantities	56pcs	112pcs	168pcs	224pcs	280pcs	336pcs	448pcs	560pcs
LED Chips brand	Philips SMD3030							
Lumens	110lm/W-150lm/W							
Materials	Die-cast aluminum+PC Lens							
Color temperature	3000K/4500K/6500K options							
CRI	75%							
IP Grade	IP65 Waterproof							
Input voltage	DC12V 24V 48V and AC110V 220-240VAC optional							
Beam angle	30 60 90 30*70 60*90 60*120° optional							
Working temperature	-25°C~+50°C							
Certificates	CE RoHS LVD EMC							
Warranty	2-5Years							
Remark	PIR Sensor/Emergency kit can be available.							