

Pull out downlights



Grnled



Feature

- 1.CREE/Bridgelux COB, CRI92
- 2.Top led driver, isolated, Free flicker.
- 3.Lifetime>5years at least
- 4.CE RoHS LVD EMC

Option

1. Emergency kits (1- 3hours duration)
2. Triac/0-10V/DALI dimmable

Specification

Model	GR-DL-7WS	GR-DL-15WS	GR-DL-20WS	GR-DL-25WS	GR-DL-7x2	GR-DL-15x2	GR-DL-20x2	GR-DL-25x2
Power	7W	15W	20W	25W	7W*2	15W*2	20W*2	25W*2
Dimension(mm)	Ø90xH80	Ø115xH105	Ø135xH125	Ø165xH165	W90xL170mm	L210*W115	L250*W140	L303*W160
Outcut(mm)	Ø75-80mm	Ø90-95mm	Ø115mm	Ø150mm	L155*W75	L190*W95	L230*W120	L280*W145
Led chips	Bridgelux / CREE COB							
Lumens output	90lm/W							
Color temperature	3000K WW; 4000-4500K NW ; 6000-6500K CW;							
Input voltage	AC100-240VAC; The low voltage such as DC12V 24V 48V can be customized							
Control gear	Included							
Power factor	>0.6/0.9							
CRI	>92							
IP Grade	IP20 Indoor use only							
Materials	Die-cast aluminum							
Beam angle	12/24/38°							
Working temperature	-25°C~+50°C							
Warranty	3-5Years							