


Surface Led Downlight



Grnled




Feature

1. Bridgelux/CREE COB. CRI90
2. Surface/Pendant installation options
3. Top led driver, free flicker, lifetime > 5 years
4. Emergency kit option
5. High voltage/DC Low voltage input options.
6. Efficiency > 89%
7. CE RoHS LVD EMC

Application



Light distribution



Specification

Model	GR-DL-10WX	GR-DL-15WX	GR-DL-20WX	GR-DL-30WX
Power	10W	15W	20W	30W
Dimension(mm)	Ø140xH155	Ø170xH180	Ø190xH195	Ø229xH225
Outcut(mm)	/			
LED Chips brand	Brigelux /CREE			
Lumens	900-950lm	1300-1350lm	1800-1900lm	2700-2800lm
Color temperature	3000K-6500K			
Input voltage	AC100-240VAC; DC12V 24V 48V can be customized			
Driver	Included.Free flicker			
Power factor	>0.6			
CRI	>90			
Dimmable	No.But Triac/0-10V/DALI dimmable can be available			
Materials	Die-cast aluminum+reflector. White/Black options			
Beam angle	60°			
Working life	50000Hrs			
Standard	Comply with CE RoHS			
Warranty	3-5Years			
Working temperature	-20°C ~ +50°C			
Installation	Surface/ Pendant installation options			
Remark				