

Surface Mounted Downlight




Feature

1. Bridgelux/CREE COB. CRI90
2. Surface/Pendant installation options
3. Top led driver, free flicker, lifetime > 5 years
4. Triac/0-10V dimmable options
5. Five colors for reflector option
6. Efficiency > 89%


Feature



Light distribution



24°	15W	3000K
H(m)	D(m)	E(lx)
1.0	0.43	2714
2.0	0.85	679
3.0	1.28	302
4.0	1.70	170
5.0	2.13	109



38°	15W	3000K
H(m)	D(m)	E(lx)
1.0	0.69	1656
2.0	1.38	410
3.0	2.07	180
4.0	2.75	105
5.0	3.44	66

Specification

Model	GR-DL-7WU	GR-DL-12WU	GR-DL-15WU	GR-DL-20WU
Power	7W	12W	15W	20W
Dimension(mm)	Ø55xH120	Ø75xH130	Ø95xH140	Ø115xH140
Outcut(mm)	/			
LED Chips brand	Brigelux /CREE			
Lumens	600-650lm	1000-1080lm	1300-1400lm	1800-1900lm
Color temperature	3000K-6500K			
Input voltage	AC100-240VAC; DC12V 24V 48V can be customized			
Driver	Included.Free flicker			
Power factor	>0.6			
CRI	>92			
Dimmable	No.But Triac/0-10V/DALI dimmable can be available			
Materials	Die-cast aluminum+reflector. White/Black options			
Beam angle	24/38°			
Working life	50000Hrs			
Standard	Comply with CE RoHS			
Warranty	3-5Years			
Working temperature	-20°C ~ +50°C			
Installation	Surface/ Pendant installation options			
Remark	Just email to us if have any other requirements or questions			