

# Linear Led High Bay Lights



## Feature

- 1.Surface/Pendant installation
- 2.PF>0.95
- 3.THd<15%
- 5.Emergency kits available
- 6.Working life>50000Hrs.

## Specification

Model	GR-HB-50WL	GR-HB-100WL	GR-HB-150WL	GR-HB-200WL	GR-HB-250WL	GR-HB-300WL	GR-HB-500WL
Power Watt	50W	100W	150W	200W	250W	300W	500W
Dimension(mm)	353*144*115	620*144*115	887*144*115	1154*144*115	1421*144*115	947*230*173	1481*230*173
Led quantities	56pcs	112pcs	168pcs	224pcs	280pcs	336pcs	560pcs
Lumens	110-130lm/W output						
Input voltage	AC100-240VAC 50/60Hz. DC12V 24V 48V can be customized as well						
Materials	Die-cast aluminum+PC Lens.						
Color temperature	3000K/4500K/6500K						
CRI	75%						
Control gear	Meanwell/philips/DONE/MOSO/ZH/SOSEN options						
Power factor	>0.95						
Beam angle	30/60/90/80*155°						
Working temperature	-25°C~+50°C						
Working life	>50000Hrs						
IP Grade	IP65 Waterproof						
Certificates	CE RoHS LVD EMC						
Warranty	2-5Years						
Remark	Triac/0-10V/DALI and emergency kits options.						